
Micro Balance ASMB 61T




AN ISO 9001:2015 CERTIFIED CO.









WindShield

Dual wind-shield design for improved airflow and protection against temperature fluctuations with an evaporated metal coating reduces static charges



Standard Accessories Ionizer & Anti-vibration pad

The balance includes an ionizer to neutralize static on charged samples. An Anti-vibration pad to ensure stable, accurate measurements.



Features:

Date & Time display function

Repeatability: 0.004mg Linearity: 0.005ma Pan Size: 30mm dia Response time : ≤ 8Sec

- 5-inch touch screen interface
- Automatic internal calibration
- Built-in advanced functions such as formulation, GLP compliance, and piece counting
- Multi-language support (7 languages)
- Multi-user password security
- Connectivity via RS232C and USB ports
- Animal weighing, Piece Counting, Percentage Weighing Totalizing Σ , High /Low Threshold weighing function.

Dimensions:

Indicator Dimension (LxWxH): 173 x 180 x 92mm

• Distance pan/top windshield: 75mm

• Winshield Internal diameter: 165mm

Weighing Chamber Size: 165 x 165 x 75mm

Dimension (LxWxH): 510 x 410 x 520mm

Net / Gross Weight: 7.5kg / 11kg

Applications: Pharmaceutical laboratories, Chemical and research labs, Material science, Environmental testing









